



## Torflex® Axles for Agricultural Equipment

### Designed to Withstand Rigorous Farming Conditions

- Independent wheel suspension and self-dampening action
- Rubber cushioning eliminates metal-to-metal contact
- Heat-treated solid steel inner bar
- Forged torsion arm for maximum strength
- Rubber cords compounded for dependability
- Easy installation with less overall maintenance
- Low profile availability for maximum road clearance
- Single or tandem axle assemblies
- Five-year limited warranty on suspension system



**GEARED FOR INNOVATION SINCE 1960**



## Torflex® Agricultural Axle Matrix

Model #	Capacity	Arm Center	Spindle	Brake	Bolt Pattern	Start Angle	Hub & Hub/Drum	Brackets	Min Overhang	Max Overhang
#12AG	5,500 to 7,000	5"	35-6D	Idler Only	6 on 6.0	45, 32, 22.5, 10, 0, 10, 22.5	Drilled & tapped for 1/2-20 wheel bolt	1" Hi-pro	15.50"	30.50"
#12AG	5,500 to 7,000	5"	35-6F	Idler Only	6 on 6.0	45, 32, 22.5, 10, 0, 10, 22.5	9/16-18 stud	1" Hi-pro	15.50"	30.50"
#12AG	5,500 to 7,000	5"	35-6B	12" x 2" Elec or Hyd	6 on 5.5 6 on 6.0	45, 32, 22.5, 10, 0, 10, 22.5	Drilled & tapped for 9/16-20 wheel bolt	1" Hi-pro	14.00"	30.50"
#13AG	8,000	6"	60-8B	Idler or 12.25" x 3.38" Elec	8 on 8.0	45, 32, 22.5, 10, 0, 10, 22.5	5/8-18 stud	1" Hi-pro	22.00"	43.00"
#13AG	8,000	6"	60-8B	Idler or 12.25" x 3.38" Hyd	8 on 8.0	45, 32, 22.5, 10, 0, 10, 22.5	5/8-18 stud	1" Hi-pro	22.00"	43.00"
#13AG	8,000	6"	60-8B	Idler or 13" x 2.5" Hyd	8 on 8.0	45, 32, 22.5, 10, 0, 10, 22.5	5/8-18 stud	1" Hi-pro	22.00"	43.00"
#13HAG	9,000 to 10,000	6"	60-8B	Idler or 12.25" x 3.38" Elec	8 on 8.0	45, 32, 22.5, 10, 0, 10, 22.5	5/8-18 stud	1" Hi-pro	22.00"	43.00"
#13HAG	9,000 to 10,000	6"	60-8B	Idler or 12.25" x 3.38" Hyd	8 on 8.0	45, 32, 22.5, 10, 0, 10, 22.5	5/8-18 stud	1" Hi-pro	22.00"	43.00"
#13HAG	9,000 to 10,000	6"	60-8B	Idler or 13" x 2.5" Hyd	8 on 8.0	45, 32, 22.5, 10, 0, 10, 22.5	5/8-18 stud	1" Hi-pro	22.00"	43.00"

- 35-6D spindle is 3,500 lbs. capacity for a 6 on 6.00" hub with 4.62" pilot that is drilled and tapped for 1/2-20 wheel bolts.
- 35-6F spindle is 3,500 lbs. capacity for a 6 on 6.00" hub with 4.62" pilot that has 9/16-18 studs and wheel nuts.
- 60-8B spindle is 6,000 lbs. capacity for an 8 on 8.00" hub with 6.00" pilot that has 5/8-18 studs and wheel nuts. Electric and hydraulic brakes are available.

- On #12AG axles, certain designs may have interference issues when using wheels wider than 10".
- The idler hubs have a grease fitting to allow grease to be added. The grease seal is installed with the lip out to allow the grease to flow out the back of the hub.
- There is no grease fitting on the two-piece brake hub and drum.
- All axles have our standard black paint finish.

