

Models and Capacities



MODELS AND CAPACITIES: 22,500 – 27,500 LBS.

Model No.	Beam	Brake	Beam Capacity**	
			Highway w/Leaf Springs	Air Ride Suspension
D-2L12	5" Light Wall	12 1/4" x 7 1/2"	22,500 Lbs.	n/a +
D-2M12	5" Medium Wall	12 1/4" x 7 1/2"	25,000 Lbs.	22,500 Lbs.
D-2H12	5" Heavy Wall	12 1/4" x 7 1/2"	27,500 Lbs.	25,000 Lbs.
D-2L16	5" Light Wall	16 1/2" x 7"	22,500 Lbs.	n/a +
D-2M16	5" Medium Wall	16 1/2" x 7"	25,000 Lbs.	22,500 Lbs.
D-2H16	5" Heavy Wall	16 1/2" x 7"	27,500 Lbs.	25,000 Lbs.

** Allowable use of axle capacity ratings (type of service and track/spring center overhang dimension, etc.) and components vary with application.

+ Light wall tube on models D-2L12 and D-2L16 is not approved for axles equipped with air ride suspensions.

Available Axle Tracks

Tracks are available from 48" to 124".

Brake Performance

The following brake models meet or exceed requirements set forth by Federal Motor Vehicle Safety Standards 121 when tested under the following conditions:

Brake Size	Wheel Load *(lbs.)	Rolling Radius (in.)	A.L. Factor (consisting of)
12 1/4" x 7 1/2"	10,000	15.7	Type 30 A/C 6" Slack Adjuster
16 1/2" x 7"	12,500	19.6	Type 30 A/C 6" Slack Adjuster

* Wheel Load per wheel end

The permitted use of axles and components, including the capacity ratings that are shown, vary with application and type of service. The capacities indicated for tires, wheels and axles should be used for general guidelines only.

Dexter Axle disclaims all warranties, whether written, oral or implied, in fact or in law (including any warranty of merchantability or fitness for a particular purpose), associated with the use of the manual and with any information presented by this manual.