



NEV-R-LUBE™

SEALED CARTRIDGE BEARING SYSTEM



Maintenance free

No bearing adjustment required

Available on TORFLEX® & Sprung axles
between 5,200 and 8,000 lbs.

Available on 6 on 5.50" and 8 on 6.50"
bolt pattern

Made in the U.S.A.

Five-year or 100,000 miles limited warranty

ISO 9001:2015 Certified



NEV-R-LUBE™
SEALED CARTRIDGE BEARING SYSTEM

WHAT IS NEV-R-LUBE™

DEXTER'S NEV-R-LUBE BEARINGS ARE COMPRISED OF OPPOSED TAPERED ROLLER BEARING CONES SEALED INSIDE OF A PRECISION GROUND CASING. NEV-R-LUBE IS A ROBUST SOLUTION DESIGNED TO ELIMINATE THE NEED TO PACK AND ADJUST BEARINGS. NEV-R-LUBE IS NOT DESIGNED FOR IMMERSION IN WATER, SUCH AS BOAT TRAILER USE.

NEV-R-LUBE is subject to periodic inspection procedures as specified in Dexter's current publication, "Operation Maintenance Service Manual".

NEV-R-LUBE SPECIFICATIONS 42MM

- D52 and D60 leaf spring axle (straight spindle only)
- #11 and #12 TORFLEX® axles
- Up to 6,000 lbs. capacity
- 6 on 5.50" bolt pattern
- 12" x 2" hub brake sizes
- Disc brake
- Use only zero offset wheels

NEV-R-LUBE ADVANTAGES

Dexter's NEV-R-LUBE bearing system is a maintenance free product that provides a worry free experience, so users can relax and focus on the road.

NEV-R-LUBE SPECIFICATIONS 50MM

- D70, D72, and D80 leaf spring axles (straight spindle only)
- #12, #12V, and #13 TORFLEX axles
- Up to 8,000 lbs. capacity
- 8 on 6.50" bolt pattern
- 12" x 2", 12-1/4" x 3-3/8", and 12-1/4" x 2-1/2" hub brake sizes
- Disc brake
- Can be used with zero to 1/2" inset wheel at 7,000 lb. capacity
- Zero offset or 0.19" inset wheel only at 8,000 lbs. capacity



NEV-R-LUBE FEATURES

- No more inner and outer bearing to repack
- Bearing pre-lubricated and resistant to contamination
- Increased durability and reliability
- No grease seal required
- Easy installation; no bearing adjustment needed
- Five-year or 100,000 miles limited warranty
- ISO 9001:2015 Certified



NEV-R-LUBE™
SEALED CARTRIDGE BEARING SYSTEM

www.dexteraxle.com



Scan to view
NEV-R-LUBE video

